

TYPE APPROVAL CERTIFICATE

Certificate No: **TAE0000498**

This is to certify: That the Electric Motor with type designation(s) EM180-series, EM220-series, EM300-series Issued to Transfluid S.P.A. Gallarate VA, Italy is found to comply with DNV GL rules for classification - Ships, offshore units, and high speed and light craft Application: e a. Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV. Issued at Hamburg on 2021-04-14 This Certificate is valid until 2026-04-13. DNV local station: Italy/Malta CMC Approval Engineer: Thomas Hartmann Arne Schaarmann **Head of Section** Topico,

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251 Revision: 2021-03 www.dnv.com Page 1 of 3

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-033242-1** Certificate No: **TAE0000498**

Product description

3-phase synchronous motor with permanent-magnet excitation controlled by frequency converter:

| General Data | |
|--------------------|-------|
| Duty type: | S1 |
| IP Rating | 65 |
| Ambient air temp.: | 45 °C |
| Insulation class: | F |

| Product | | Cooling Method ¹⁾ | P _N [kW] ²⁾ | P _{Peak} [kW] | U _N [AC] | Rated speed [rpm] |
|-----------|---------------|---------------------------------|-----------------------------------|------------------------|---------------------|----------------------|
| 180-4 | GATF5936DQ | Α | 3 | 4 | 68 | 3000 |
| | | Α | 1.5 | 2 | 34 | 1500 |
| | GATF5936DQ000 | T W | 4 | 5 | 62 | 3000 |
| | | W | 2.5 | 3 | 37 | 1500 |
| 180-8 | GATF5936DL | Α | 6 | 8 | 68 | 3000 |
| | | A | 4 | 5 | 35 | 1500 |
| | GATF5936DL000 | W | 8 | 10.5 | 60 | 3000 |
| | | W | 5 | 7 | 37 | 1500 |
| 180-12 | GATF5936DM | Α | 8 | 12 | 57 | 3000 |
| | | Α | 5 | 7 | 29 | 1500 |
| | | A | 6 | 8 | 30 | 1500 |
| | GATF5936DM000 | W | 12 | 15.5 | 60 | 3000 |
| | | W | 8 | 10 | 32 | 1500 |
| | GATF5936DD | Α | 15 | 20 | 77 | 3000 |
| | | Α | 8 | 10 | 39 | 1500 |
| 220-20 | | Α | 10 | 15 | 39 | 1500 |
| | GATF5936DD000 | T - W - | 10 | 15 | 39 | 1500 |
| | | W | 20 | 25 | 68 | 3000 |
| | | W | 30 | 35 | 79 | 3000 |
| 220-20EVO | GATF5936DD010 | W | 15 | 20 | 34 | 1500 |
| 220-35 | GATF5936DE | Α | 28 | 35 | 158 | 3000 |
| | | Α | 20 | 25 | 78 | 1500 |
| | GATF5936DE000 | w | 25 | 30 | 78 | 1500 |
| | | W | 35 | 45 | 159 | 3000 |
| 300-50 | GATF5936DF | Α | 40 | 50 | 199 | 3000 |
| | | A | 30 | 35 | 103 | 1500 |
| | GATF5936DF000 | - W | 35 | 45 | 105 | 1500 |
| | | W | 50 | 65 | 178 | 3000 |
| 300-75 | GATF5936DG | Α | 60 | 75 | 242 | 3000 |
| | | A | 40 | 50 | 122 | 1500 |
| | GATF5936DG000 | W | 45 | 55 | 123 | 1500 |
| | | W | 75 | 100 | 242 | 3000 |
| | | W | 100 | 130 | 252 | 3000 |

¹⁾ A- Air cooled; W-water-cooled

Application/Limitation

When use as ship's propulsion motor documentation according to DNV Rules must be submitted for approval for each project with special attention to DNV RU-Ship Pt.4 Ch.8 Sec. 5 [3].

Product certification shall be carried out for motors of 300kW and above, as required by DNV rules Pt.4 Ch.8 Sec.1 Table 3. Excess torque- and current capabilities of the permanent-magnet motor as per makers technical data sheet. Motor characteristics and load requirements to be coordinated in the project application.

Type Approval documentation

Form code: TA 251 Revision: 2021-03 www.dnv.com Page 2 of 3

²⁾ Power at 40°C derating as per maker's specification



Job Id: 262.1-033242-1 TAE0000498 Certificate No:

Tests carried out

Visual inspection, IP degree, Overspeed, Resistance measurements of windings, Withstand voltage test, Measurement of winding resistance, Insulation resistance, Overload test, Temperature rise test.

Marking of product

Type designation - technical data including rated voltage - RPM, rated power - ambient temperature rated current - rated frequency - insulation class - IP class, cooling method.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials. The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval

anu.

ad after 2 yc.

All and a second and a Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE

Form code: TA 251 Revision: 2021-03 www.dnv.com Page 3 of 3